

# SAFETY DATA SHEET

Printing date 3/4/2016

acc. to OSHA HCS



**K-Deer LA, Inc.**

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE MIXTURE OF THE COMPANY UNDERTAKING

1.1	Product Identifier	<b>BLASTITE, BLITZBLAST, DURATRED, FASTBLAST, NIAGARA BLAST, EXOBLAST, DURALUM G52E, G52E P, G52E RK, G82, G82P, GW, GW VIT, HBD, HC, K5, LBD, RF, DCF, LT, LTR, C ART, C AR RK, C PRT, C PR RK, LT C AT, LT C ART, LT C ARRK, LT C PT, LT C PRT, XA, SK</b>
	GHS Product Identifier	<b>DURABLU C ABRT, C PBRT, LT C ABRT, LT C PBRT, C A BR RK, C PBR RK, LT C ABRRK, LT CPBR RK</b>
	Chemical Name	<b>BLASTITE, BLITZBLAST, DURATRED, FASTBLAST, NIAGARA BLAST, EXOBLAST, DURALUM G52E, G52E P, G52E RK, G82, G82P, GW, GW VIT, HBD, HC, K5, LBD, RF, DCF, LT, LTR, C ART, C AR RK, C PRT, C PR RK, LT C AT, LT C ART, LT C ARRK, LT C PT, LT C PRT, XA, SK</b>
	CAS No.	<b>DURABLU C ABRT, C PBRT, LT C ABRT, LT C PBRT, C A BR RK, C PBR RK, LT C ABR</b>
	ENECs No.	<b>RK, LT CPBR RK</b>
	REACH Registration No.	<b>Brown Aluminum Oxide</b>
1.2	Relevant Identified Uses of The Substance of Mixture And Uses Advised Against	Mixture
	Identified Use(s)	Mixture
	Uses Advised Against	Not Available
1.3	Details of The Supplier Of The Safety Data Sheet	
	Company Identification	K-Deer La. In
	Address	9358 Stephens St. Pica Rivera, CA, 90680
	Telephone	562-568-0588
	E-Mail (Competent Person)	helenpan@kdeerla.com
1.4	Emergency Telephone Number -	Tel 562-568-0588, 562-889-7862





# SAFETY DATA SHEET

Printing date 3/4/2016

acc. to OSHA HCS

## SECTION 2: HAZARDS IDENTIFICATION

2.1	Classification Of The Substance Or Mixture
2.1.1	Regulation (EC) No. 1272/2008 (CLP) – (3.9/2)
2.1.2	Directive 67/548/EEC & Directive 1999/46/EC - HARMFUL
2.2	Label Elements
2.2.1	Label Elements According to Regulation (EC) No. 1272/2008 (CLP)
	GHS Product Identifier(EU)
	Hazard
	Signal word(s) WARNING
	Pictogram(s) 
	Hazard Statement(s) H373: May cause damage to organs through prolonged or repeated exposure.
	Precautionary Statement(s) P260: Do not breathe dust P340+P341: IF INHALED: if breathing is difficult, remove victim to fresh air and keep at rest in a Position comfortable for breathing.
2.2.2	Label Elements According to Directive 67/548/EEC & Directive 1999/45/EC
	Hazard Symbol 
	Risk phrase R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.
	Safety Phrases S38: In case of insufficient ventilation, wear suitable Respiratory equipment.
2.3	Other Hazards
	GHS Classification (USA): Hazardous under OSHA Hazard Communication Standard-HARMFUL (Carcinogen)
	HMIS: Health-1, Flammability-0, Reactivity-0
	Hazard Statement(s) H335: May cause respiratory irritation.
	Precautionary Statement(s) P304 + P341: IF INHALED: if breathing is difficult, remove Victim to fresh air and keep at rest in a position comfortable for breathing.
	WHIMS/GHS Classification (Canada): Hazardous under WHMIS.
	D2B-Material Causing Other Toxic Effects (Carcinogen)
	Hazard Statement(s) H373: May cause damage to organs through prolonged or Repeated exposure.

# SAFETY DATA SHEET

Printing date 3/4/2016

acc. to OSHA HCS

	Precautionary Statement(s)	
	P261: Avoid breathing dust/fume/gas/mist/vapours/spray.	
	P280: Wear protective gloves/protective clothing/eye protection/face protection.	
	P304 + P341: IF INHALED: if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.	
2.4	Additional Information	See Section 16 for additional dust hazard information.
	Potential Health Effects	
	Inhalation	Irritation of the respiratory tract (Dust). Crystalline silica is implicated in pulmonary disease due to prolonged and/or multiple exposures.
	Skin Contact	Mechanical irritation.
	Eye Contact	Mechanical irritation, corneal scratches.
	Ingestion	Harmful if swallowed; mechanical and chemical irritant.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

EC Classification No. 1272/2008/EC and GHS Classification					
Hazardous Ingredient(s)	%W/W	CAS No.	EC No.	REACH Registration No.	Hazard Pictogram(s) and Hazard Statement(s)
Aluminum Oxide	>90	1344-28-1	215-691-6	NA	None          None
Impurities: = SiO <sub>2</sub> + Si + C + Fe + Al = <1.0% * - <i>May contain crystalline silica</i>					
EC Classification No. 67/548/EEC					
Hazardous Ingredient(s)	%W/W	CAS No.	EC No.	REACH Registration No.	Hazard Pictogram(s) and Risk(R) Phrase(es)
Aluminum Oxide	>90	1344-28-1	215-691-6	NA	None          None
Silicon Dioxide*	<5	7631-86-9	231-545-4	NA	R48/20
Impurities: = SiO <sub>2</sub> + Si + C + Fe + Al = <1.0% * - <i>May contain crystalline silica</i>					
3.3 <b>Additional Information</b> - For full text of H phrases see section 16. For full text of R phrases see section 16. Non-Hazardous ingredients are not listed and make up the balance of the product.					

## SECTION 4: FIRST AID MEASURES

### 4.1 Description of First Aid Measures

# SAFETY DATA SHEET

Printing date 3/4/2016

acc. to OSHA HCS

Inhalation	Remove patient from exposure. Keep patient at rest and give oxygen if breathing difficult. If symptoms develop, obtain medical attention.
Skin Contact	Remove contaminated clothing immediately and drench affected skin with plenty of water. If irritation (redness, rash, blistering) develops, get medical attention.
Ingestion	Avoid ingestion. Do not induce vomiting. Get immediate medical attention.
<b>4.2 Most Important Symptoms And Effects, Both Acute And Delayed</b>	<b>Acute:</b> Cough and Shortness of breath. <b>Delayed and Chronic Effects:</b> This product contains crystalline silica, which poses an inhalation hazard, especially upon chronic exposure. Silicosis may cause an emphysemic-like illness with serious health concerns. Crystalline silica is also considered a carcinogen by several national and international agencies.
<b>4.3 Indication Of The Immediate Medical Attention And Special Treatment Needed</b>	Treat symptomatically.

## SECTION 5: FIRE-FIGHTING MEASURES

<b>5.1 Extinguishing Media</b>	
Suitable Extinguishing Media	Extinguisher suitable for ordinary combustible materials. Class A extinguishing agents.
Unsuitable Extinguishing Media	None known.
<b>5.2 Special Hazards Arising From The Substance Or Mixture</b>	A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions.
<b>5.3 Advice for Fire-Fighters</b>	Extinguish preferably with dry chemical, foam or water spray.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

<b>6.1 Personal Precautions, Protective Equipment And Emergency Procedures</b>	Avoid dust generation. Ensure full personal protection (including respiratory protection) during removal of spillages.
<b>6.2 Environmental Precautions</b>	Ventilation recommended.
<b>6.3 Methods And Material For Containment And Cleaning Up</b>	Collect mechanically and dispose of according to Section 13. Transfer to a lidded container for disposal or recovery. Avoid dust generation.
<b>Reference To Other Sections</b>	Ensure adequate ventilation.
<b>6.4</b>	See Also Section 7, 8, 13.
<b>6.5 Additional Information</b>	None

# SAFETY DATA SHEET

Printing date 3/4/2016

acc. to OSHA HCS


## SECTION 7: HANDLING AND STORAGE

7.1	<b>Precautions For Safe Handling</b>	Avoid contact with skin and eyes. Wash hands before eating, drinking or smoking. Avoid accumulation of dust. Use only in well-ventilated areas.
7.2	<b>Conditions For Safe Storage, Including Any Incompatibilities</b>	Store in the original container in a cool, dry well ventilated area. Keep containers tightly sealed.
	Storage Temperature	Ambient.
	Storage Life	Not available
	Incompatible Materials	Separate from oxidizers (oxygen), (explosives), (halogens), (compressed air) (acids), (bases) (and food chemicals) etc. in transport (and storage).
7.3	<b>Specific End Use(s)</b>	Consult the supplier.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>8.1 Control Parameters</b>						
<b>8.1.1 Occupational Exposure Limits</b>						
Substan	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m <sup>3</sup> )	STEL (ppm)	STEL (mg/m <sup>3</sup> )	Note:
Aluminum Oxide	1344-28-1	NE	10	NE	NE	ACGIH
		NE	15 (vacated)	NE	NE	OSHA
Silicon Dioxide*	7631-86-9	NE	16 (Calculated)*	NE	NE	OSHA - 5% SiO <sub>2</sub>
		NE	6 (Calculated)*	NE	NE	OSHA - 5% Quartz
* - Based on 80 mg/m <sup>3</sup> ÷ 5% SiO <sub>2</sub> for Amorphous SiO <sub>2</sub> and 30 mg/m <sup>3</sup> ÷ 5% SiO <sub>2</sub> for Quartz						
<b>8.1.3 PNECs and DNELs</b>						
No PNECs or DNELs available for product						




### 8.2.2 Personal Protection Equipment

	<b>Respirators</b>	Avoid breathing dust. Assess exposure concentrations of all materials involved in the workplace. If concentrations exceed the exposure limits listed in Exposure Guidelines or irritation or other symptoms experienced, follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149.
---	--------------------	---

# SAFETY DATA SHEET

Printing date 3/4/2016

acc. to OSHA HCS

	<b>Eye Protection</b>	Avoid eye contact. Wear protective eyewear (goggles, face shield, or safety glasses).
	<b>Gloves</b>	Wear protective gloves.
	<b>Body Protection</b>	Avoid skin contact. Wear suitable protective clothing and gloves.
	<b>Engineering Controls</b>	Provide sufficient ventilation, particularly in closed rooms. Maintain employee exposure below applicable permissible exposure limits.
	<b>Other</b>	Remove contaminated, saturated clothing immediately. Contaminated clothing should be thoroughly cleaned.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information On Basic Physical And Chemical Properties

Appearance	Black or Green solid granular product	Color	Black or Green
Odor	Odorless	Odor Threshold (ppm)	Not available
Melting Point (°C)/	Not available	Boiling Point/Boiling Range (°C)	Not available
Freezing Point (°C)			
Flash Point (°C)	No Data	Explosive Limit Ranges	Not available
Auto Ignition Temperature (°C)	Not available	Decomposition Temperature (°C)	4892°F
Explosive Properties	None	Oxidizing Properties	Not
Flammability (Solid, Gas)	Not available	Ph (Value)	available
Evaporation Rate	N/A N/A	Vapor Pressure (mm Hg)	Not
Vapor Density	Insoluble	Density (g/ml)	
Partition Coefficient (NOctanol/Water)	Not available	Solubility (Other)	available
		Viscosity (mPa.s)	Not
			available

**9.2 Other Information** Volatile Organic Chemical (VOC) Content – Not Available.

## SECTION 10: STABILITY AND REACTIVITY

<b>10.1</b>	<b>Reactivity</b>	Slight
<b>10.2</b>	<b>Chemical Stability</b>	Stable under normal conditions.
<b>10.3</b>	<b>Possibility Of Hazardous Reactions</b>	Not available
<b>10.4</b>	<b>Conditions To Avoid</b>	Not available

# SAFETY DATA SHEET

Printing date 3/4/2016

acc. to OSHA HCS

<b>10.5</b>	<b>Incompatible Materials</b>	Not available
<b>10.6</b>	<b>Hazardous Decomposition Product(s)</b>	Not available

## SECTION 11: TOXICOLOGICAL INFORMATION

Substance	CAS No.	LD50 (Oral, Rat)	LC50 (Inhalation, Rat)	LD50 (Dermal, Rat)
Aluminum Oxide	1344-28-1	NE	NE	NE
Silicon Dioxide*	7631-86-9	10000 mg/kg	NE	5000 mg/kg

**Avoid accumulation of dust.**

<b>11.1</b>	<b>Information on Toxicological Effects</b>	
<b>11.1.2</b>	<b>Mixtures</b>	
	Acute Toxicity	
	<i>Inhalation</i>	Inhalation of the dust may cause breathlessness, coughing, tightness of the chest and difficulty in breathing.
	<i>Skin Contact</i>	Prolonged contact may cause skin abrasion, redness, and itching.
	<i>Eye Contact</i>	Eye irritant. May cause tearing and redness.
	<i>Ingestion</i>	May cause headache, nausea and vomiting.
	Irritation	Causes eye irritation. May cause respiratory irritation. May cause transient irritation.
	Corrosively	Not to be expected.
	Sensitization	No data.
	Repeated Dose Toxicity	No data.
	Carcinogenicity	Crystalline silica and titanium dioxide are suspect or confirmed carcinogens under ACGIH, NTP IARC, and/or the state of California (respirable particles).
	Mutagenicity	No data.
	Toxicity for Reproduction	No data.
<b>11.2</b>	<b>Other Information</b>	None

## SECTION 12: ECOLOGICAL INFORMATION

<b>12.1</b>	<b>Toxicity</b>	No data
<b>12.2</b>	<b>Persistence and Degradability</b>	No data
<b>12.3</b>	<b>Bioaccumulative Potential</b>	The product has low potential for bioaccumulation.
<b>12.4</b>	<b>Mobility In Soil</b>	No data
<b>12.5</b>	<b>Results Of PBT And vPvB</b>	No data.

# SAFETY DATA SHEET

Printing date 3/4/2016

acc. to OSHA HCS

<b>12.6</b>	<b>Assessment Other Adverse Effects</b>	No data.
-------------	---	----------

## SECTION 13: DISPOSAL CONSIDERATIONS

<b>13.1</b>	<b>Waste Treatment Methods</b>	Solid or chemical waste generators must determine whether a discarded waste is classified as a hazardous waste. U.S. EPA guidelines for the classifications determination are listed in 40 CFR parts 261.3. Disposal should be in accordance with local, state or national legislation. Containers must not be punctured or destroyed by burning, even when empty.
<b>13.2</b>	<b>Additional Information</b>	None

## SECTION 14: TRANSPORT INFORMATION

<b>Land Transport(ADR/RID) (c)(d)</b>		<b>Land Transport(Within USA) (b)(d)</b>	
UN Number	None	UN Number	None
Proper Shipping Name	Not classified as dangerous for transport.	Proper Shipping Name	Not classified as dangerous for transport.
Transport Hazard Class(es)	None	Transport Hazard Class(es)	None
Packing Group	None	Packing Group	None
Hazard Label(s)	None	Hazard Label(s)	None
Environmental Hazards	None	Environmental Hazards	None
Special Precautions For	None	Special Precautions For User	None
<b>Sea Transport(IMDG) (c)</b>		<b>Air Transport(ICAO/IATA) (c) (d)</b>	
UN Number	None	UN Number	None
Proper Shipping Name	Not classified as dangerous for	Proper Shipping Name	Not classified as dangerous for
Transport Hazard Class(es)	None	Transport Hazard Class(es)	None
Packing Group	None	Packing Group	None
Hazard Label(s)	None	Hazard Label(s)	None
Environmental Hazards	None	Environmental Hazards	None
Special Precautions For	None	Special Precautions For User	None



# SAFETY DATA SHEET

Printing date 3/4/2016

acc. to OSHA HCS

(b)-ORM-D may be applicable within the USA for package sizes less than 30kg.

(c)-Consult with transport provider.

(d)-Check relevant regulations for Special Provisions.

**Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

## SECTION 15: REGULATORY INFORMATION

### 15.1 Safety, Health And Environmental Regulations/Legislation Specific For The Substance Or Mixture

#### 15.1.1 EU Regulations

Authorisations And/Or Restrictions On Use Consult the supplier.

European Union (EINECS/ELINCS) All chemicals listed.

German WGK Number Not available

#### 15.1.2 National Regulations

##### USA

TSCA (Toxic Substance Control Act) Listed

SARA 311/312 -Hazard Categories Acute Health, Chronic Health

SARA 302 -Extremely Hazardous Listed -None

Substances Listed -None

SARA 313 -Toxic Chemicals Listed -None

CERCLA (Comprehensive Environmental Listed -None

Response Compensation and Liability Act) Listed -None

CAA (Clean Air Act 1990) Listed -None

CWA (Clean Water Act) Listed -None

State Right to Know Lists Listed. -Silicon Dioxide, Quartz, MA, MN, NJ, PA.

Proposition 65 (California) - This product contains the following substance(s) known to the state of California to cause cancer and/or reproductive harm; Silicon Dioxide (silica, crystalline), Titanium Dioxide (respirable).

##### Canada

WHMIS Classification Class D Division 2, Subdivision B, Material Having Other Toxic Effects (Irritant).

Canada(DSL/NDSL) Listed. - DSL.

Canada Ingredient Disclosure List (CIDL) Listed as required.

**15.2 Chemical Safety Assessment** Irritant (Skin, Eye, Respiratory system), Suspect Carcinogen (Inhalation - Repeated Exposure only)

## SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.



# SAFETY DATA SHEET

Printing date 3/4/2016

acc. to OSHA HCS

## LEGEND

ACGIH	American Conference Of Governmental Industrial Hygienists	NA	Not Applicable, Not Available
	Australian Inventory Of Chemical Substances		National Institute For Occupational Safety And Health
AICS		NIOSH	Health
atm	Atmosphere (Pressure Unit)	NFPA	National Fire Prevention Association
BOD	Biological Oxygen Demand	NTP	National Toxicology Program
CAS	Chemical Abstracts Service	OC	Open Cup
CC	Closed Cup	OSHA	Occupational Safety And Health Administration
CDTA	Chemical Drug And Trafficking Act	Part	Partition
COC	Cleveland Open Cup	PEL	Permissible Exposure Limits
COD	Chemical Oxygen Demand	ppb	Parts Per Billion
coeff.	Coefficient	PPE	Personal Protective Equipment
CFR	Code Of Federal Regulations	ppm	Parts Per Million
CPR	Cardio-Pulmonary Resuscitation	psi	Pounds Per Square Inch
DEA	Drug Enforcement Agency	RCRA	Resource Conservation And Recovery Act
DOT	Department Of Transportation	RO	Reportable Quantity
DSCL	Dangerous Substances Classification And	RTK	Right To Know
EEC	European Economic Community	SARA	Superfund Amendments And Reauthorization Act
FDA	Food And Drug Administration	STEL	Short-Term Exposure Limit
HMIS	Hazardous Materials Information System	SUSDP	Standard For The Uniform Scheduling Of Drugs And Poisons
IDLH	Immediate Danger To Life Or Health	TDG	Transportation Of Dangerous Goods
kg	Kilogram	TPQ	Threshold Planning Quantity
L	Liter	TQ	Threshold Quantity
LC50	Median Lethal Concentration	TSCA	Toxic Substances Control Act
LD50	Median Lethal Dose	TWA	Time-Weighted Average
LEL	Lower Explosive Limit	UEL	Upper Explosive Limit
mg	Milligram	WES	Workplace Exposure Standard (New Zealand)
mL	Milliliter	WHMIS	Workplace Hazardous Material Information System

**References:** RTECS, CAS Registry, EINECS/ESIS, *Casarett & Doull's Toxicology*, *Goldfrank's Toxicological Emergencies*, Manufacturer Information



# SAFETY DATA SHEET

Printing date 3/4/2016

acc. to OSHA HCS

## Risk Phrases and Safety Phrases

R36/37/38: Irritating to eyes, respiratory system and

skin. R36/38: Irritating to eyes and skin.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36: Wear suitable protective clothing.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

## Hazard Statement(s) and Precautionary Statement(s)

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation

H373: May cause damage to organs through prolonged or repeated exposure:

P260: Do not breathe dust.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P304 + P341: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

**Training Advice:** None

### Additional Information:

- ☐ The accumulation of airborne dust particles may lead to health and safety risks in some cases. The use of good industrial practices will mitigate this risk.
- ☐ The health risks from inhalation of dust particles vary; this is due to particle concentration, exposure length, number of exposures and type of particles inhaled. Please read Sections 2,4,6,7 and 8 of the MSDS to understand these potential risks. Wear personal protective equipment and follow storage and handling procedures to maintain a safe workplace.
- ☐ In rare instances, combustible dusts may represent a potential explosion hazard when airborne. This hazard is often associated with organic dust such as foodstuffs and coal, but may also occur with mineral products. While the majority of our products would be considered non-combustible, the overall airborne environment should be considered when determining the need for mitigation from this potential hazard. Consult recognized experts when necessary in order to determine any possible hazard.

**Please read the MSDS for specific information concerning these hazards, and contact us with any further questions. We appreciate your continued business.**

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. ChemTel Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. ChemTel Inc. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

