



**ENVIRO
ABRASIVES**

ENVIRONMENTAL ABRASIVES

Sandblasting Equipment and Media Supplies

(208) 947-1351 | Boise, Idaho

COPPER SLAG

Manufactured by:

KLEEN BLAST



**CARB Certified
Mil Spec MIL-A-22262B (SH)
No Free Silica**

Typical Composition

SiO ₂	38.1%
Fe ₂ O ₃	27.4%
CaO	22.8%
Al ₂ O ₃	5.7%
MgO	3.9%
Other Oxides	1.9%

Copper Slag by Kleen Blast is an Iron Alumina Silicate that is black in color, with angular to sub-angular granules.

It has been water-quenched to remove most of the soluble metals and harden the particles at the cooling stage, then fresh water washed, removing unusable fines, dust and soluble chlorides.

TYPE	SIZE	APPLICATIONS	PROFILE (MIL.)
Fine	30-60	Feather & Brush-Off Smooth Finish Auto Body Water Blast Systems Light Mill Scale	.05-1.5
Med/Fine	35	Most Light Work Mill Scale New Structural Steel	1.5-3.0
Medium	16-30	General Purpose Shipyards Heavy Mill Scale Concrete Structural Steel	2.5-5.0
Med/Large	16	Heavy Scale Rust/Heavy Paint Exposed Aggregate Concrete	4.0-5.0
Large	8-12	Heavy Scale Rust/Heavy Paint Exposed Aggregate Concrete	5.0+

enviroabrasives.com

4301 S Federal Way, Boise, ID 83716, USA